

FR525 - Bizflame 88/12 Iona Xtra 7oz FR Coverall

Collection: Bizflame™ 88/12

Range: Flame Resistant

Shell Fabric: Bizflame 88/12: 88% Cotton, 12% Nylon

Outer Carton: 14

Product Information

Offering superior breathability and outstanding moisture management while still meeting CAT 2 with an ATPV of 8.2 cal/cm², this durable coverall offers guaranteed flame resistance for the life of the garment. The high quality construction, premium fabric and deluxe features all designed to keep you comfortable and safe.

Bizflame™ 88/12

The fabric is soft yet hard wearing and the quality of the construction is excellent. The global fit contributes to the overall appeal of this garment, which is sold in over 130 countries.

Flame Resistant

This industry leading flame resistant range provides multi-standard protection for hazardous environments. These state of the art products are the result of years of experience combined with advanced technology and market research. Commitment to the health, safety and comfort of the wearer can be seen in the wide range of products suitable for all climates and end uses.

Standards

NFPA® 2112

NFPA® 70E

ASTM F1506

ASTM F1959/F1959M-12 (ATPV 8.2 CAL/CM2 (HAF 69.1%))

CSA-Z96 Compliant Class 1 (Level FR)



Features

- Lightweight and comfortable
- Sew on HiVisTex Flame™ Ultra reflective tape with fabric backing
- Guaranteed flame resistance for life of garment
- Centre front two-way breakaway brass zip
- Strap and elastic fasteners for attaching H2S monitor
- Lowered reflective tape on back to allow for logo application
- Dual hazard protection
- 8 pockets for ample storage
- ARC2
- 40+ UPF rated fabric to block 98% of UV rays

BIZFLAME™ 88/12

FR.IW



FR525 BIZFLAME 88/12 2" XTRA FR COVERALL
 CSA-Z96 COMPLIANT CLASS 1 LEVEL FR
 NFPA® 2112
 NFPA® 70E
 ASTM F1506
 ASTM F1959/F1959M-12 ATPV 8.2 CAL/CM²
 (HAF 69.1%)

- Fabric-backed HiVisTex Flame™ Ultra reflective striping
- Lightweight and comfortable
- Guaranteed flame resistance for life of garment
- Centre front two-way breakaway brass zip
- Strap and elastic fasteners for attaching H2S monitor
- Lowered reflective tape on back to allow for logo application
- Dual hazard protection

Bizflame 88/12: 88% Cotton, 12% Nylon, 7oz

7oz

CAT 2
ATPV 8.2

CSA Z96
CLASS 1
LEVEL FR

NFPA 2112

NFPA 70E

NEW



2" CONTRAST STRIPING

REG	TALL
34-70	34-70
34-70	34-70
34-70	34-70
34-70	34-70

ASTM F1506
NFPA 2112
NFPA 70E